

HIGH PRODUCTION, TRACK MOUNTED TOOL CARRIER



- MULCHER
- ROOT RAKE
- BUCKET

ENGINE

Make and Model	Cat® 3126 DITA/240 hp
Type of Fuel	No. 2 Diesel
No. of Cylinders	6 cylinder inline
Bore and Stroke	4.33" x 5.0"
Displacement	7.2 liters (450 cubic in.)
Compression Ratio	17:1
Fuel Induction	Direct Injection

DELTA HYDROSTATIC DRIVE SYSTEM

The engine provides torque to the pumps through the pump drive gear box. Four pump drives are directly coupled to the Cat® 3126 engine. Separate electronically controlled hydrostatic variable displacement pumps and motors offer precise travel control and easy servicing. Hydrostatic drive provides maximum productivity of mulcher deck.

DIMENSIONS

Track Gauge	82.5"
Operating Height	10' 1"
Machine Width	9' 6"
Machine Length (overall)	27' 9" (w/mulcher)
Ground Clearance	14.8"
Weight	39,000 total lbs.

CONTROLS

Electronic controls adjust machine speed to take advantage of all available engine power. This maintains full power for the mulcher. It maintains engine RPM in optimum operating range and balances the two track drive systems for straight travel without machine drift. Self diagnosing for quick troubleshooting.

CAPACITIES

Fuel Tank	64.6 Gal
Crankcase and filter	5.5 Gal
Final Drives (each)	4 Gal
Cooling System	6 Gal
Hydraulic Tank (refill)	28 Gal

CYLINDER SPECIFICATIONS

Heavy duty lift	Two 4-3/4" Bores with 2" rods
Heavy duty tilt	One 5-1/2" Bore with 3" rods

Cat® is a registered trademark of Caterpillar Corp.

OSCILLATING UNDERCARRIAGE

Keeps more track on the ground for maximum traction and stability. Reduces frame impact and improves traction over a rigid undercarriage design. Swing link idler permits horizontal idler movement, absorbing shock loads and maintaining proper track tension, while eliminating the need for shims and wear strips.

FECON SPECIFICATIONS

Will slab cut trees and stumps of all sizes. The machine has a rated capacity to continuously cut 6" diameter trees. The 240 hp Cat® engine will process approximately 552 Cubic ft. of wood into mulch per hour, while maintaining a continuous working pressure of 3000 psi, with peak pressure of 4200 psi.

STANDARD EQUIPMENT

Cab: sound suppressed with air pressurization and rollover protective structure (ROPS)
Crankcase guard
Heater/defroster with temperature control
Lights: two ROPS mounted, forward facing halogen lamps
Rearview mirror
Heavy-duty perforated radiator guard
Sealed and lubricated track with two piece master link
32" double bar grouser track shoes
Sprocket guards
Track guiding guards
Windshield and back window washers and wipers
Quick couplers

PLANETARY FINAL DRIVES

Isolated from machine weight and ground induced shock loads by track roller frame pivot shafts. Externally mounted for easy maintenance and service.

For local dealers please call:

Delta Machine Products, Inc.

3000 Sidney Lanier Drive
Brunswick, GA 31525
(912) 264-1553 fax(912)264-1503

Delta Machine Products, Inc.

P.O. Box 648
Lawrenceville, GA 30046
(770) 963-9200 fax (770) 339-2931

E-mail: deltamp@aol.com

Visit our Web site: www.deltamp.com

These units are serviced by the Cat® dealer network and carry a 12 month powertrain warrant